


# HOW TO USE ...

## SURFACE

Raging Vinyl decals can apply on any smooth and not so smooth surface, such as walls, glass, metal, wood, concrete...Before applying Raging decals, make sure that the surface is dry and free of dust and dirt !!!



❶ White backing

❷ Vinyl decal

❸ Transfer tape

## CAUTION :

Before applying on freshly painted walls, allow 2 weeks for the paint to dry!

If your vinyl decal is fairly large, get a friend to help you set it up! That's also much more fun !


Note : additional tips & instructions are available online at : [www.RagingVinyl.com](http://www.RagingVinyl.com)

Raging Vinyl decals are a new smart, elegant & exciting way to decorate interiors and change the entire look of a room in a fingersnap. Easy to set-up Raging decals are also easy to remove without damaging surfaces. Simply follow the instructions.


## SET - UP



❶ Lay your Raging decal on a hard, flat surface and rub firmly over the decal with a squeegee (credit card, rubber spatula...). This will strengthen the bond between the vinyl decal and the transfer tape




❷ Remove the white backing, making sure the vinyl decal sticks properly to the tape.



❸ Arrange the vinyl decal on the desired surface. Smooth the top edge onto the surface and firmly smooth out the tape all the way down, avoiding bubbling and wrinkles



❹ Finish the application by rubbing over the entire vinyl decal in order to remove any air bubble and activate the bond between the vinyl graphic and the surface



❺ Remove transfer tape from one corner & slowly roll along the surface. if part of the decal stick to the tape, simply roll back, repress firmly & continue peeling away again.



❻ Remove air bubbles (if any) by rubbing over the decal with a clean cloth (you can also poke bubbles with a needle and then smooth it out). Rub very firmly on textured surfaces !

Watch demo video & get deco tips :

